



Koura
Klea®

Quick Guide

Products



Air Conditioning

Klea® 134a (R-134a) Refrigerant

Klea® 32 (R-32) Refrigerant

Klea® 407A (R-407A) Refrigerant

Klea® 407C (R-407C) Refrigerant

Klea® 407H (R-407H) Refrigerant

Klea® 410A (R-410A) Refrigerant



Refrigeration

Klea® 125 (R-125) Refrigerant

Klea® 32 (R-32) Refrigerant

Klea® 404A (R-404A) Refrigerant

Klea® 407A (R-407A) Refrigerant

Klea® 407C (R-407C) Refrigerant

Klea® 407H (R-407H) Refrigerant

Klea® 410A (R-410A) Refrigerant

Klea® 448A (R-448A) Refrigerant

Klea® 507 (R-507) Refrigerant



Automotive

Klea® 134a (R-134a)



Introduction

Building on a proud history of innovation across more than fifty years, we continue to invest in developing lower GWP refrigerant options in order to provide customers with the benefits and characteristics they need.

The relationship we have with our customers is key to our success. Through our dedicated sales and customer service teams we are able to offer the highest standards of customer service to meet the most demanding customer needs across the world.



Air Conditioning

A leading air conditioning
refrigerant supplier

**Our Klea® brand is trusted by major
manufacturers and aftermarket
professionals the world over.**

Our success in the air conditioning industry is built on a long history of product quality, reliability and the very best levels of customer and technical support. Klea® products are approved by major equipment manufacturers and used with confidence by aftermarket professionals across the globe.



Refrigeration

A world leader in refrigerants

Our Klea® refrigerants are supplied to major manufacturers and a large share of the aftermarket servicing sector across commercial refrigeration, automotive and stationary air conditioning applications.



Automotive

Worldwide, Koura's Klea® 134a is used in over 12,000,000 new vehicles every year.

Having established the world's first and largest commercial R-134a production plant, our continued success in the automotive sector is built on product quality, reliability and the highest levels of customer and technical support.

That's why Klea® 134a is trusted by many of the leading industry names, as well as a large share of the aftermarket servicing sector around the world.



Klea® 134a (R-134a) Refrigerant



Klea®134a refrigerant is widely accepted as the most appropriate alternative for R-12 over the majority of the application range for both retrofit and new equipment. A very good match to R-12 for air conditioning, high and medium temperature usage. It can be used in hybrid cascade systems for supermarkets and is being used in some of the HFO blends in order to bring lower flammability and better

Klea® 134a (R-134a) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	102.03	lbm/lbmol	102.03
Critical Temperature	°C	101.06	°F	213.91
Critical Pressure	bara	40.59	psia	588.75
Critical Density	kg/m ³	511.90	lb/ft ³	31.96
Normal Boiling Point	°C	-26.074	°F	-14.933
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	216.97	BTU _{IT} /lb	93.28
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	5.2581	lb/ft ³	0.33
Liquid Vapour Pressure at 25°C	bara	6.6538	psia	96.51
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.0032364	°F ⁻¹	0.00180
Speed of Sound* for Saturated Vapour at 25°C	m/s	144.26	ft/s	473.29
Adiabatic Exponent* for Saturated Vapour at 25°C		1.23		1.23
Latent Heat of Vapourisation at 25°C	kJ/kg	177.780	BTU _{IT} /lb	76.43
Saturated Vapour Density at 25°C	kg/m ³	32.350	lb/ft ³	2.020
Saturated Vapour Density at 0°C	kg/m ³	14.428	lb/ft ³	0.901

* Vapour composition as per bulk refrigerant at dew

Klea[®] 32 (R-32) Refrigerant



Klea[®] 32 refrigerant is of interest as both a blend component for alternatives to R-22 and R-502 such as Klea[®] 407A and Klea[®] 410A, and as an attractive low GWP candidate for air conditioning. It can be blended with HFOs to improve performance.

Klea[®] 32 (R-32) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	52.02	lbm/lbmol	52.02
Critical Temperature	°C	78.11	°F	172.59
Critical Pressure	bara	57.82	psia	838.61
Critical Density	kg/m ³	424.00	lb/ft ³	26.47
Normal Boiling Point	°C	-51.651	°F	-60.972
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	381.86	BTU _{IT} /lb	164.17
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	2.9879	lb/ft ³	0.19
Liquid Vapour Pressure at 25°C	bara	16.896	psia	245.06
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.00465	°F ⁻¹	0.00258
Speed of Sound* for Saturated Vapour at 25°C	m/s	203.72	ft/s	668.37
Adiabatic Exponent* for Saturated Vapour at 25°C		1.68		1.68
Latent Heat of Vapourisation at 25°C	kJ/kg	270.910	BTU _{IT} /lb	116.47
Saturated Vapour Density at 25°C	kg/m ³	47.339	lb/ft ³	2.955
Saturated Vapour Density at 0°C	kg/m ³	22.091	lb/ft ³	1.379

* Vapour composition as per bulk refrigerant at dew

Klea® 407A (R-407A) Refrigerant



Klea® 407A refrigerant is an energy efficient, low GWP refrigerant designed for use in medium and low temperature supermarket applications. It is suitable for new installations and retrofits on existing R-22, R-507 and R-404A units. Klea® 407A meets the GWP requirements beyond 2030 under the EU F-Gas Regulations for industrial and commercial refrigeration.

Klea® 407A (R-407A) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	90.11	lbm/lbmol	90.11
Critical Temperature	°C	82.26	°F	180.06
Critical Pressure	bara	45.15	psia	654.87
Critical Density	kg/m ³	498.86	lb/ft ³	31.14
Atmospheric Bubble Point	°C	-45.007	°F	-49.0
Atmospheric Dew Point	°C	-38.593	°F	-37.5
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	238.36	BTU _{IT} /lb	102.48
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	4.8824	lb/ft ³	0.30
Liquid Vapour Pressure at 25°C	bara	12.531	psia	181.7
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.0042611	°F ⁻¹	0.00237
Speed of Sound* for Saturated Vapour at 25°C	m/s	149.33	ft/s	489.93
Adiabatic Exponent* for Saturated Vapour at 25°C		1.34		1.34
Latent Heat of Vapourisation at 25°C	kJ/kg	172.17	BTU _{IT} /lb	74.02
Saturated Vapour Density at 25°C	kg/m ³	49.749	lb/ft ³	3.11
Saturated Vapour Density at 0°C	kg/m ³	22.441	lb/ft ³	1.40

* Vapour composition as per bulk refrigerant at dew

Klea® 407C (R-407C) Refrigerant



All of the Klea® 407 series refrigerants are based on blends of the three HFC refrigerants R-32, R-125 and R-134a. Klea® 407C refrigerant has been formulated as a good match to the existing HCFC refrigerant R-22 for use in air conditioning, chilling and refrigeration applications and was the first of the R-22 alternatives to be used on a commercial scale. Suitable for retrofit and original equipment usage. Klea® 407C meets the GWP requirements beyond 2030 under the EU F-Gas Regulations for industrial and commercial refrigeration. Composition (wt%) R-32/R-125/R-134a = 23/25/52. Please note that not all products are available in all markets.

Klea® 407C (R-407C) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	86.20	lbm/lbmol	86.20
Critical Temperature	°C	86.03	°F	186.85
Critical Pressure	bara	46.29	psia	671.42
Critical Density	kg/m ³	484.20	lb/ft ³	30.23
Atmospheric Bubble Point	°C	-43.627	°F	-46.5
Atmospheric Dew Point	°C	-36.629	°F	-33.9
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	256.29	BTU _{IT} /lb	110.18
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	4.6306	lb/ft ³	0.29
Liquid Vapour Pressure at 25°C	bara	11.903	psia	172.6
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.0040236	°F ⁻¹	0.00224
Speed of Sound* for Saturated Vapour at 25°C	m/s	154.97	ft/s	508.43
Adiabatic Exponent* for Saturated Vapour at 25°C		1.33		1.33
Latent Heat of Vapourisation at 25°C	kJ/kg	188.42	BTU _{IT} /lb	81.01
Saturated Vapour Density at 25°C	kg/m ³	43.77	lb/ft ³	2.73
Saturated Vapour Density at 0°C	kg/m ³	19.689	lb/ft ³	1.23

* Vapour composition as per bulk refrigerant at dew

Klea® 407H (R-407H) Refrigerant



With increasing regulation on HFCs, there is greater demand for refrigerants that are safe, energy efficient, allow for easy economical conversion and comply with various global regulations. In addressing this demand, Koura has launched the Klea® 407H. With its ease of retrofit and performance. Klea® 407H is a cost effective, “drop in” solution for many refrigerant systems. Our considered solution has been designed specifically for an efficient future.

Klea® 407H (R-407H) Refrigerant Physical Properties

Chemical Name		Difluoromethane/ Pentafluoroethane/ 1,1,1 Tetrafluoroethane
Chemical Formula		CH2F2/CHF2-CF3/CF3-CH2F
GWP100	IPCC 4th AR/5th AR	1495/1380
Molecular Weight	bara	46.29
Boiling Point @ 1.013 bar bubble point / dew point	°C	-44.7/-37.6
Critical Temperature	°C	86.5
Critical Pressure	bar	48.5
Critical Density	kg/m ³	464.1
Critical Volume	dm ³ /kg	2.155
Liquid Density ³	kg/m ³	111.2
Vapour Density ³	kg/m ³	41.86
Heat of Vaporization ³	kJ/kg	199.02
cp liq. ³	kJ/(kg K)	1.585
cp vap. ³	kJ/(kg K)	1.176
Temp. Glide @ NBP	K	7.0
ASHRAE 34 safety class		A1

² All thermo-physical data are based on Refprop 9.0
3sat. @25°C

Klea[®] 410A (R-410A) Refrigerant



Klea[®] 410A refrigerant is a leading high pressure alternative to R-22, comprising R-32 and R-125, for air conditioning and refrigerant applications for new equipment. Composition (wt%) R-32/R-125 = 50/50. Please note that not all products are available in

Klea[®] 410A (R-410A) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	72.59	lbm/lbmol	72.59
Critical Temperature	°C	71.35	°F	160.43
Critical Pressure	bara	49.02	psia	710.96
Critical Density	kg/m ³	459.53	lb/ft ³	28.69
Atmospheric Bubble Point	°C	-51.443	°F	-60.6
Atmospheric Dew Point	°C	-51.364	°F	-60.5
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	279.12	BTU _{IT} /lb	120.00
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	4.1742	lb/ft ³	0.26
Liquid Vapour Pressure at 25°C	bara	16.574	psia	240.4
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.0051708	°F ⁻¹	0.00287
Speed of Sound* for Saturated Vapour at 25°C	m/s	161.86	ft/s	531.04
Adiabatic Exponent* for Saturated Vapour at 25°C		1.58		1.58
Latent Heat of Vapourisation at 25°C	kJ/kg	190.6	BTU _{IT} /lb	81.94
Saturated Vapour Density at 25°C	kg/m ³	65.972	lb/ft ³	4.12
Saturated Vapour Density at 0°C	kg/m ³	30.576	lb/ft ³	1.91

* Vapour composition as per bulk refrigerant at dew

Klea® 125 (R-125) Refrigerant



Klea® 125 refrigerant is a main building block for blended refrigerants used as replacements for R-502 and R-22. These blends include Klea® 410A which has become a leading replacement for R-22, Klea® 407C which was one of the first commercially available blends suitable for both retrofit and original equipment use of R-22 systems and Klea® 407A, a lower GWP alternative to Klea® 404A and Klea® 507. Please note that not all products are available in all

Klea® 125 (R-125) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	120.02	lbm/lbmol	120.02
Critical Temperature	°C	66.02	°F	150.84
Critical Pressure	bara	36.18	psia	524.70
Critical Density	kg/m ³	573.58	lb/ft ³	35.81
Normal Boiling Point	°C	-48.089	°F	-54.560
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	164.1	BTU _{IT} /lb	70.55
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	6.79	lb/ft ³	0.42
Liquid Vapour Pressure at 25°C	bara	13.779	psia	199.85
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.0055069	°F ⁻¹	0.00306
Speed of Sound* for Saturated Vapour at 25°C	m/s	117.32	ft/s	384.91
Adiabatic Exponent* for Saturated Vapour at 25°C		1.36		1.36
Latent Heat of Vapourisation at 25°C	kJ/kg	110.390	BTU _{IT} /lb	47.46
Saturated Vapour Density at 25°C	kg/m ³	90.557	lb/ft ³	5.653
Saturated Vapour Density at 0°C	kg/m ³	42.070	lb/ft ³	2.626

* Vapour composition as per bulk refrigerant at dew

Klea® 404A (R-404A) Refrigerant



Klea® 404A refrigerant is an established alternative to R-22 and R-502. Please note that for reduced GWP, Klea® 407A offers a good alternative.

Composition (wt%) R-143a/R-125/R-134a = 52/44/4.
Please note that not all products are available in all

Klea® 404A (R-404A) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	97.60	lbm/lbmol	97.60
Critical Temperature	°C	72.05	°F	161.68
Critical Pressure	bara	37.29	psia	540.83
Critical Density	kg/m ³	486.54	lb/ft ³	30.37
Atmospheric Bubble Point	°C	-46.2	°F	-51.2
Atmospheric Dew Point	°C	-45.5	°F	-49.8
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	199.61	BTU _{IT} /lb	85.82
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	5.48	lb/ft ³	0.34
Liquid Vapour Pressure at 25°C	bara	12.5	psia	182.0
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.00495	°F ⁻¹	0.00275
Speed of Sound* for Saturated Vapour at 25°C	m/s	133.8	ft/s	438.94
Adiabatic Exponent* for Saturated Vapour at 25°C		1.37		1.37
Latent Heat of Vapourisation at 25°C	kJ/kg	138.99	BTU _{IT} /lb	59.75
Saturated Vapour Density at 25°C	kg/m ³	65.27	lb/ft ³	4.07
Saturated Vapour Density at 0°C	kg/m ³	30.47	lb/ft ³	1.90

* Vapour composition as per bulk refrigerant at dew

Klea® 448A (R-448A) Refrigerant



Klea® 448A refrigerant is an excellent low-GWP, highly energy efficient and non-flammable refrigerant for low and medium temperature in commercial refrigeration: supermarket systems, vending machines (plug-ins) and other applications. Composition (wt%) R-32/R-125/R-134a = 20/40/40. Please note that not all products are available in all markets.

Klea® 448A (R-448A) Refrigerant Physical Properties

Property	S.I. Units	Value
Chemical Notation		26% R-32 / 26% R-125 / 21% R-134a / 7% R-1234ze / 20% R-1234yf
Critical Temperature	°C	83.7
Critical Pressure	bar	46.6
Liquid Density 0°C	kg/m ³	1192.5
ANSIASHRAE Standard 36-1992 Safety Group Classification		A1
Relative Molar Mass	kg/mol	189.9
Vapour Density 25°C	kg/m ³	1.553
GWP		1273
ODP		Non-ozone depleting
REACH		Registered
ATEL/ODL (kg/m ³)	kg/m ³	0.39
Practical Limit (kg/m ³)	kg/m ³	0.39
Low Flammability Level		Non-flammable

* Vapour composition as per bulk refrigerant at dew

Klea® 507 (R-507) Refrigerant



Klea® 507 refrigerant is a viable alternative to R-22 and R-502 for new and retrofit applications, Klea® 507 offers good benefits in flooded systems. For a reduced GWP alternative, Klea® 407A is a good refrigerant in supermarket and other commercial applications. Composition (wt%) R-125/R-143a = 50/50. Please note that not all products are available in all markets.

Klea® 507 (R-507) Refrigerant Physical Properties

Property	S.I. Units	Value	British Units	Value
Molecular Weight	kg/kmol	98.86	lbm/lbmol	98.86
Critical Temperature	°C	70.62	°F	159.11
Critical Pressure	bara	37.05	psia	537.36
Critical Density	kg/m ³	490.77	lb/ft ³	30.64
Atmospheric Bubble Point	°C	-46.741	°F	-52.1
Atmospheric Dew Point	°C	-46.741	°F	-52.1
Latent Heat of Vapourisation at Atmospheric Pressure	kJ/kg	196.8	BTU _{IT} /lb	84.61
Saturated Vapour Density at Atmospheric Pressure	kg/m ³	5.5861	lb/ft ³	0.35
Liquid Vapour Pressure at 25°C	bara	12.826	psia	186.0
Coefficient of Volumetric Thermal Expansion for Saturated Liquid at	°C ⁻¹	0.0050859	°F ⁻¹	0.00283
Speed of Sound* for Saturated Vapour at 25°C	m/s	131.85	ft/s	432.58
Adiabatic Exponent* for Saturated Vapour at 25°C		1.38		1.38
Latent Heat of Vapourisation at 25°C	kJ/kg	135.76	BTU _{IT} /lb	58.37
Saturated Vapour Density at 25°C	kg/m ³	68.888	lb/ft ³	4.30
Saturated Vapour Density at 0°C	kg/m ³	32.251	lb/ft ³	2.01

* Vapour composition as per bulk refrigerant at dew

For more information visit
Klea.com

Klea®

Product Information

Disclaimer

Information contained in this publication, or as otherwise supplied to the Users is believed to be accurate and given in good faith, but it is for the User to satisfy itself of the suitability for its own particular purpose. Koura gives no warranty as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Mexichem accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patent, Copyright and Design cannot be assumed. Klea® is a brand of Koura and is a registered trademark of Mexichem SAB de C.V.

© Koura 2021. All rights reserved. Not to be reproduced without the consent of the copyright owner.

Klea® is a brand of Koura and is a registered trademark of Mexichem SAB de C.V.

kouraglobal.com